



## H2-Z003R11 H2 Filling station

The H2 filling station enables the refueling of gaseous hydrogen from up to 4 different H2 storage tanks (cylinder bundles). The filling process is simple and uncomplicated, it can be started quickly and runs automatically. Depending on the pre-pressure in the H2 storage tanks, a vehicle can be refueled up to a maximum of 300 bar.



*The actual product may differ slightly from the image.*

### Standard version

---

- Paint: blue-anthracite

### Special features

---

- Gas type: H2

## Advantages & functions

### Electrical data:

- Electrical connecting cable:  $\geq 1,5 \text{ mm}^2$  (AWG 15)
- Cable with plug 16 A

### Pressure sensors:

- Measuring range: 0 - 400 bar

### Connection to the vehicle:

- 1x 3 m Hose with connection couplings to the vehicle TK16-H35. (Hose lengths and connection couplings can be specified individually)

### Gas supply:

- 4x hydrogen bundles, max. pressure 300 bar (gas and gas cylinders not included in the scope of delivery)

## Technical data

Dimensions (W x H x D)	1,200 x 2,280 x 800 mm
Weight	250 kg (empty)
Sound level	< 70 dB
Ambient temperature	0 to +40 °C
Storage temperature	-20 to +60 °C
Ambient moisture	< 90 % r. h. non-condensing
Protection class	IP 44
Height	mm max. 2000 m above sea level
Operating voltage	230 V AC
Frequency	50/60 Hz

## Technical drawing

